DEM1205



Design By =

Naoto Fukasawa

Collection =

Design





Colors & Finishes =



Materials =

- Head and arms in painted aluminum
- Lower head diffuser in thermoplastic
- Internal springs and external tension control cables in aluminum
- Floor support stem in aluminum
- Floor base in weighted steel with painted aluminum cover


Specifications —

Delivered lumens	392lm
Light output ratio	43.56lm/W
Power consumption	9W
Led type	8.5W Array*
CCT (Correlated Color Temperature)	2700K
CRI (Color Rendering Index)	>90
Life expectancy	50000Hrs
Control type	DIMMABLE (On Head) / No Motion Sensor
Input Voltage	120-240V
Driver	Plug-In

Features & Accessories =


- Fully adjustable arms and head
- Tiltable and rotatable diffuser
- Interchangeable plug options accommodate most electrical outlets for global versatility

Dimensions =



Light distribution

Direct



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Packaging =

3 Boxes

1 x 42" x 14" x 2-5/8" / 5.51 lbs - 106.5 cm x 35.5 cm x 6.5 cm / 2.5 kg

1 x 11-15/16" x 11-15/16" x 3-13/16" / 9.17 lbs - 30.1 cm x 30.1 cm x 9.5 cm / 4.16 kg

1 x 41-13/16" x 1-11/16" x 1-11/16" / 1.54 lbs - 106 cm x 4 cm x 4 cm / .7 kg

Luminaire weight =

9.81 lbs / 4.45 kg

Warranty =

5 year limited warranty

