

PALMA

Design by Antoni Arola.

Reference

3736.

Application

Pendants

Installation type

Surface mounted

Description

Nature takes control of the space. With the pendant lamps, the interior ambiance takes on a life of its own with the possibility of integrating plants with the lighting compositions.

Diffuser

Blown-glass diffuser

Materials

Profile: Aluminum

Canopy: Steel

Flowerpot: PMMA (thermoplastic polymer)

Finishes




3736-18 Graphite (ADAPTA RF 9913 WX)



3736-93 White (RAL 9016)

Sketch



Electrical characteristics

6 x LED 4.6W 500mA

AND

1 x LED 2W 500mA



Total 29.6 W



VIBIA



Light source: 2700K CRI >90 2742 lm 94.34 lm/W

Fixture: 2057.53 lm 69.51 lm/W

Driver included: CC - Constant Current 500 mA 120-277V 50/60Hz

Electronic dimming: 0-10V

Optional dimming: DALI or Lutron ECO

Technical characteristics

- Plants not included


Installation and assembly

Please see the installation manual

Light distribution

General lighting

Lamp for general lighting that equally distributes the light in all directions.



Photometric data

Efficiency : 1

Coordinate system : CG

Total flux : 1912.81 lm

Maximum value : 65.09 cd/klm

Light position : C=0.00 G=1.00

Symmetry on the planes : Asymmetric

Isolux : Isolux (Floor)

Light position :

X=0.00m Y=0.00m Z=2.50m

Certificates

