

RC55K4RKT2

Code:

7453021622974

Specifications

Panel Parameters

Size	55" diagonally
Backlight	DLED direct Type
Maximum resolution	3840x2160
Contrast ratio (Typ)	1200:1
Response time(Typ)	6.5 ms
Display scale	16:09
Viewing angle(CR>10)	Typ(H:178°,V:178°)
Display Colors	1.07G
Color Gamut(NTSC)	≥NTSC 68%
LCM Center Luminance of White	Min:250cd/m2, Typ:300cd/m2
Local dimming	nonsupport
Uniformity of Luminance	≥75% (1/9 point)

2. Hardware Information

ATV	NTSC-M
DTV	DVB-T2
CPU Frame	ARM Cortex-A53 1.1GHz/Quad core
GPU	G52 MC1/Dual core
RAM(DDR)	1 GB
ROM(Flash)	512MB
Audio power(Output)	8W+8W
WIFI(Type)	2T2R
Tuner type	screw-thread
USB 2.0	2
USB 3.0	-
VGA	-



AV In	1
YPbPr In	-
CI	-
PC Audio	-
RJ-45	1
Earphone	1
Audio In	-
Audio Out	-
Video Out	-
SPDIF Out	1 optical
Bluetooth(Version)	-
HDMI	4
Others	-

3. Software Function

Channel list	YES
Channel edit	YES
Picture freezing	NO
MTS/NICAM	MTS
Sleep time setting	YES
Teletext	NO
PVR	NO
EPG	NO
V_CHIP/Parental Guidance	YES
CC(Closed caption)	YES
AD(Audio description)	NO
TTS(Text to Speech)	YES
CI+	NO

DOLBY	YES
HDMI-ARC	YES
HDMI-CEC	YES
HDMI-MHL	NO
Operation system	Linux
OTA	YES
Hotel mode	NO

4. Structure Information

Size (without stand) LxWxH	1226x89x720mm
Size (with stand) LxWxH	1226x350x764mm
Size (carton) LxWxH	1321x120x804mm
Net Weight (without stand)	10.9kg
Net Weight (with stand)	11.1kg
Gross Weight (without stand)	14.7kg
Gross Weight (with stand)	14.7kg
Size (Wall hanging)	300x300mm

5. Power Management & Safety & Certificate

Power input	100-240VAc
Fire rating	UL94-HB75
Standby power	≤0.5W
Rated power	130W
Working condition	Temperature : 5°C~40°C humidity : 20%~80% atmosphere : 86KPa~106KPa
Storage condition	Temperature : -20°C~55°C humidity : 20%~80% atmosphere : 86kPa~106kPa

6. Accessory

Stand(Optional)	1PCS
Remote control	1PCS
Instruction	1PCS
Warranty card(Optional)	1PCS
Battery(Optional)	2PCS