

# Filter Gravel 1/2" - 1/4"

## ONatural rounded or angular stone/rock (1/2" - 1/4")

Gravel provides essential support and flow distribution in filter systems through graduated layers ranging from 2-50mm. Larger sizes at the bottom prevent media loss while supporting even water distribution during operation and backwashing.



### APPLICATIONS

- Underbedding

Shipping Weight	99 - 101 lbs/cu.ft. (1586 - 1618 g/L)	Color	Yellow to Brown
Specific Gravity	2.7 gm/cc	Hardness	6

### SUGGESTED OPERATING CONDITIONS

Flow Rate	
Working Service	Depends on fluid viscosity. Contact ResinTech

**SAFETY DATA SHEETS (SDS)**

Safety Data Sheets (SDS) are available for all products on the ResinTech website. They contain important health and safety information that may be needed to protect your employees and customers from any known health and safety hazards associated with our products. We recommend that you secure and study the pertinent MSDS for our products and any other products being used.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith. However we do not make any guarantee or warranty. We caution against using these products in an unsafe manner or in violation of any patents; further we assume no liability for the consequences of any such actions.

Safety Data Sheets (SDS) are available at [resintech.com](https://www.resintech.com)

Page 2 of 2

Last Update: 06-Jun-26

