

# MBD-95-HP



Meets NSF/ANSI/CAN 61

REACH Registered

MBD-95-HP

Physical Form < 50 mesh (300 µm) %	Spherical Beads < 1	Uniformity	Gaussian
---------------------------------------	------------------------	------------	----------

**SUGGESTED OPERATING CONDITIONS**

Minimum Bed Depth	24 in. (61.0 cm)	Flow Rate	
Maximum Pressure Loss	25 psi (172 kPa)	Working Service	1-5 gpm/cu.ft. (8-40 BV/h)
Operating pH Range	2.0 to 12.0		

**PACKAGING**

**Standard**

7 cu.ft. Drum | 42 cu.ft. Supersack  
1 cu.ft. Bag | 5 cu.ft. Drum

**Metric**

25L Bag | 140L Drum

**SAFETY DATA SHEETS (SDS)**

Safety Data Sheets (SDS) are available for all products on the ResinTech website. They contain important health and safety information that may be needed to protect your employees and customers from any known health and safety hazards associated with our products. We recommend that you secure and study the pertinent MSDS for our products and any other products being used.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith. However we do not make any guarantee or warranty. We caution against using these products in an unsafe manner or in violation of any patents; further we assume no liability for the consequences of any such actions.

Safety Data Sheets (SDS) are available at [resintech.com](http://resintech.com)

