

AGC-F400 AW

Granular activated carbon, acid-washed Calgon filtrasorb 400, bituminous coal, iodine number 1000 (mg/m)

ResinTech AGC-F400 AW is Calgon Filtrasorb 400 coal-based granular activated carbon, Iodine number 1000 (mg/m)



APPLICATIONS

- Dechlorination
- Taste & Odor Correction
- Organics

Physical Form	Carbonaceous Granules	Shipping Weight	37 - 39 lbs/cu.ft. (593 - 625 g/L)
< 50 mesh (300 µm) %	< 5%	Color	Black
Moisture Retention (%)	20 to 30		

CARBON SPECIFICATIONS

Acid Washed	Acid Washed	Conductivity (uS/cm)	500
Min. Iodine Number (mg/gm)	1000		

SUGGESTED OPERATING CONDITIONS

Maximum Temperature	212°F (100°C)	Flow Rate	
Operating pH Range	5.0 to 8.0	Working Service	Depends on fluid viscosity, Contact ResinTech

SAFETY DATA SHEETS (SDS)

Safety Data Sheets (SDS) are available for all products on the ResinTech website. They contain important health and safety information that may be needed to protect your employees and customers from any known health and safety hazards associated with our products. We recommend that you secure and study the pertinent MSDS for our products and any other products being used.

These suggestions and data are based on information we believe to be reliable. They are offered in good faith. However we do not make any guarantee or warranty. We caution against using these products in an unsafe manner or in violation of any patents; further we assume no liability for the consequences of any such actions.

Safety Data Sheets (SDS) are available at resintech.com

