

Tray Delivery Carts

High Volume Series - Stainless Steel

**Models 831, 832, 835
836, 837**



Model 835

Low Profile Design For Safe View During Transport

- Perimeter bumper protects walls, furnishings and doors
- Accepts 14" x 18" (356 x 457 mm) or 15" x 20" (381 x 508 mm) trays
- 5" (127 mm) ledge spacing
- Doors conveniently open 270° for easy tray access
- Designed for rugged acute care foodservice use
- Easy to clean and sanitize. Simply wipe down or steam clean
- Removable ledge panels for easy cleaning



Specifications

Unit is of welded and riveted type 304 stainless steel construction and accommodates either 14" x 18" (356 x 457 mm) or 15" x 20" (381 x 508 mm) meal trays. Back, top and sides are 18-gauge stainless steel. Floor/base are 18-gauge stainless steel and have drain(s) to facilitate cleaning. Tray compartment(s) feature louvered vents on side and back panels. Angle style tray ledges are 16-gauge stainless steel welded to 14-gauge stainless steel upright frames with 5" (127 mm) spacing. Ledge frame assemblies are adjustable to accommodate 14" x 18" or 15" x 20" (508 mm) trays and are removable to facilitate cleaning. Door(s) are of double pan construction, with 1" (25 mm) rigid fiberglass insulation for sound deadening and have a stainless steel flush-mount paddle latch. Door(s) are mounted on heavy-duty stainless steel lift-off hinges which allow 270° door swing. Unit shall feature a non-marking full-perimeter bumper and stainless steel push handle. Casters are extra-load 8" (203 mm) diameter, two fixed and two swivel with brakes, with 2" (51 mm) wide non-marking rounded cushion tread wheels. Unit is NSF listed.

Models 831 and 832 only:

Casters are extra-load 6" (152 mm) diameter, two fixed and two swivel with brakes, with 2" (51 mm) wide non-marking rounded cushion tread wheels.

Spec. #

AIA #

Lakeside Manufacturing, Inc.


4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.

800-558-8565 • 414-902-6400 • Fax 414-902-6446 • info@eLakeside.com • www.eLakeside.com/foodservice

Models
831, 832
835, 836
837

Tray Delivery Carts

High Volume Series - Stainless Steel



AutoCAD drawings available through KCL CADalog

Optional Accessories

- 8" diameter casters (Models 831 and 832)
- Extra push handle
- Identification card holder
- Decorative laminate door panels

Product Information

Model	Tray Capacity*	Ledge Spacing	Interior Compartments	Overall			Casters		Ship Weight	
				W	D	H	Type	Dia.	Lbs.	(Kg.)
831	18 ea. 14" x 18" or 15" x 20" (356 x 457) or (381 x 508)	5" (127)	1	36 ³ / ₄ " (908)	26" (664)	56" (1422)	2 Swivel 2 Rigid	6"	300	(136)
832	20 ea. 14" x 18" or 15" x 20" (356 x 457) or (381 x 508)	5" (127)	1	36 ³ / ₄ " (908)	26" (664)	61" (1549)	2 Swivel 2 Rigid	6"	320	(145)
835	24 ea. 14" x 18" or 15" x 20" (356 x 457) or (381 x 508)	5" (127)	2	51" (1299)	34" (867)	41" (1041)	2 Swivel 2 Rigid	8"	425	(193)
836	28 ea. 14" x 18" or 15" x 20" (356 x 457) or (381 x 508)	5" (127)	2	51" (1299)	34" (867)	46" (1168)	2 Swivel 2 Rigid	8"	450	(205)
837	32 ea. 14" x 18" or 15" x 20" (356 x 457) or (381 x 508)	5" (127)	2	51" (1299)	34" (867)	51" (1295)	2 Swivel 2 Rigid	8"	475	(216)

Measurements in () denote metric millimeters, unless otherwise specified.



Lakeside Manufacturing, Inc.
 4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.
 800-558-8565 • 414-902-6400 • Fax 414-902-6446
 info@eLakeside.com • www.elakeside.com/foodservice