

Open Pan & Tray Racks

Economy Series - Stainless Steel

Models 125, 126, 135, 136, 155, 156

Model 155

Durable, Efficient Storage System With All-Welded Stainless Steel Construction

- All-welded construction - no assembly required
- Both channel and angle style ledges are electronically welded to the uprights to withstand continual use
- Tie bars are welded to the uprights for added rigidity and integrity
- A variety of casters are available from economical 4" (102 mm) corner stem to heavy duty 5" (127 mm) recessed plate with No-Mark® polyurethane wheels
- Welded stainless steel design is easy to sanitize and maintain

Ideal for...

- Hotels, central kitchens, hospitals and schools
- Refrigerated or dry storage
- Convenient sheet pan and tray transport



Specifications

Unit is of all-welded construction and accommodates 18" x 26" pans or 14" x 18" pans and trays. Corner upright legs, and top and bottom frame are of .104 x 3/4" x 1-1/4" angle stainless steel. Pan/tray ledges are of 16-gauge stainless steel and are welded to upright legs front and back. Top and bottom corner frame joints have 20-gauge reinforcing gussets welded in place for extra rigidity. Unit has a 16-gauge x 1/2" x 1/2" angle stainless steel horizontal brace welded to upright legs at open ends front and back. Casters are 4" diameter swivel stem type, corner mounted to corner legs for upright stability. Unit is NSF listed.

Spec. #

AIA #

Lakeside Manufacturing, Inc.

4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.

800-558-8565 • 414-902-6400 • Fax 414-902-6446 • info@eLakeside.com • www.eLakeside.com/foodservice

Open Pan & Tray Racks


Economy Series - Stainless Steel

Models

125, 126

135, 136

155, 156



AutoCAD drawings available through KCL CADalog

Model Information

Model	Pan Capacity		Ledge Description			Overall Size			Casters		Ship Wt.	
	Full	Half	Type	Spacing	Width	W	D	H	Type	Diameter	Lbs.	(Kg)
125	35 ea.	70 ea.	Channel	1-7/16" (37)	1/2" (13)	21" (533)	27-1/4" (692)	57-1/2" (1460)	Corner Stem	4" (102)	64	(29)
126	41 ea.	82 ea.	Channel	1-7/16" (37)	1/2" (13)	21" (533)	27-1/4" (692)	67-1/2" (1715)	Corner Stem	4" (102)	70	(31.8)
135	16 ea.	32 ea.	Angle	3" (76)	1-5/16" (33)	21" (533)	27-1/4" (692)	57-1/2" (1460)	Corner Stem	4" (102)	62	(28.1)
136	20 ea.	40 ea.	Angle	3" (76)	1-5/16" (33)	21" (533)	27-1/4" (692)	67-1/2" (1715)	Corner Stem	4" (102)	68	(30.8)
155	10 ea.	20 ea.	Angle	5" (127)	1-5/16" (33)	21" (533)	27-1/4" (692)	57-1/2" (1460)	Corner Stem	4" (102)	50	(22.7)
156	12 ea.	24 ea.	Angle	5" (127)	1-5/16" (33)	21" (533)	27-1/4" (692)	67-1/2" (1715)	Corner Stem	4" (102)	55	(25)

Optional Accessories

- Set of four corner leg bumpers
- Welded pan top vertical rod

Measurements in () denote metric millimeters, unless otherwise specified.



Lakeside Manufacturing, Inc.
 4900 West Electric Avenue • West Milwaukee, WI 53219 U.S.A.
 800-558-8565 • 414-902-6400 • Fax 414-902-6446
 info@eLakeside.com • www.elakeside.com/foodservice