

# D6™

## 6-STAGE HVLP TURBINE

PAIR IT WITH YOUR FAVORITE FUJI SPRAY GUN

#5070	T70™ Bottom Feed
#5175G	T75G™ Gravity Feed
#9600-G	G-XPC™ Side Mounted Gravity Feed



*Unmatched Precision. Unbeatable Efficiency. Undiluted.*

The Fuji Spray® D6™ sets a new benchmark in spray finishing with a powerful 6-stage motor rated at 11.5 PSI, delivering precise control and to atomize high-viscosity coatings with virtually no thinning required. Built for serious professionals, the D6™ is designed for durability in both workshop and job-site environments.

### WHAT MAKES IT DIFFERENT

- 6-Stage Motor - 11.5 PSI to atomize coatings with little to no dilution
- Smart Select Control Panel - one-touch pressure settings from 1-stage (3 PSI) to 6-stage (11.5 PSI) for precise control
- Advanced 2 stage filtration
- Easy Pause Remote - pauses the turbine from up to 75ft to minimize interruptions

### KEY FEATURES

- Powerful 6-stage motor (11.5 PSI)
- Smart Select Control Panel with 6 pre-set pressure settings
- Advanced 2-stage turbo filtration with check filter light
- Easy Pause remote control (remote range - 75ft)
- Heat Dissipation Technology
- Noise-reducing case design
- Fold-away spray gun holder
- Ideal for high-viscosity materials
- Suitable for waterborne and solvent-based coatings
- 2+1 year warranty on parts and labor

### SPECIFICATIONS

Motor Type	1-stage (3 PSI) to 6-stage (11.5 PSI)
Wattage, Voltage Hertz, Ampere	1700W, 110-120V 60 Hz, 15 Amp
Weight	25.57 lbs
Dimensions	18" x 15" x 11"
Filtration	Foam & HEPA (2-Stage)
Compatible Hose	30ft with quick-connect & air control valve