Datasheet



1-Phase Linear M

Size	766x34x35mm
Lumen	1300lm
LED Type	SMD
Wattage	10W
ССТ	2700/3000K
UGR	1
Protective class	2
LED Chip lifetime	50.000h
Material	Polycarbonate
Driver	on/off included
SDCM	<6
CRI	90
Efficacy (Im/w)	130
IP Rating	IP20
Voltage	220-240V
Frequency	50/60Hz
Installation	Track
Beam angle	60°
Weight(kg)	0.36

Color	Art.No
0	V114010T7W
•	V114010T7B



Description

1-phase linear luminaire with CCT switch, switchable, 766x34x35mm, rated power 10W, IP20, 1300 lm, SMD LED, 2700/3000K, CRI >90, incl. on/off driver.

MANAGE

ΕΧΡΕСΤΑΤΙΟΝS

BRIGHT


Linear track spotlight for installation in 1-phase tracks. Efficient general lighting for living spaces, hallways, small retail and storage areas where a rotationally symmetric deep-wide beam light distribution is required. Suitable for all areas where homogeneous illumination and easy adjustment of the lighting to the use and conditions of the rooms are desired.

Perfectly combinable with 1-phase track spots and versatile thanks to the CCT switch.


Protection class: II, Protection rating: IP20.

Voltage: 220-240V AC, Beam angle: 60°, lifespan: 50.000 hours. Article number: V114010T7W, V114010T7B.

Technical drawing



Light Distribution





Disclaimer

All technical data as well as weight and dimension specifications are based on standard values and have been carefully prepared. We reserve the right to make technical changes at any time to reflect progress. Product images are for illustrative purposes and may differ from the original. Errors excepted. As of: 13/03/2025. Orders are subject to our General Terms and Conditions of Sale, available at https://www.vysnlighting.com/de/pages/agb