



Weight: 2.4 lbs

Project:	Type:
Prepared By:	Date:

Technical Specifications

Performance

Product Type:
Emergency Driver

L70 Lifespan:
50,000-Hour LED lifespan based on IES LM-70 results

Electrical

Driver:
Constant Current 120V-347V 50/60 Hz; 120V: 0.0553mA; 208V: 0.033mA; 240V: 0.0304mA; 277V: 0.0286mA

Power Factor:
0.84

Input Power (Max):
10W

Dimmable:
Yes, dimmable down to 10% on compatible 0-10V dimming systems. See Dimmer Compatibility List. Requires separate 0-10V DC dimming circuit.

Input Voltage:
120-347V

Operating Frequency:
50/60Hz

Operating Temperature:
0°F to 122°F (0°C to 50°C)

Battery:
Lithium Ion 14.8V/180mAh

Emergency Operation:
90 minutes

Emergency Power:
25W

Installation

Mounting Method:
Recessed

Construction

Shape:
Rectangle

Finish:
White

Enclosure Material:
Steel

Compliance

Listings:
UL Listed

Environment:

Suitable for use indoors in dry and damp environments.

California Title 20 Compliant:
Can be used to conform with the requirements of California Title 20

California Title 24 JA8 Compliant:
No

California Energy Commission (CEC) Status:
Lawful for Sales in California

IESNA LM-79 & LM-80 Testing:
RAB LED luminaires and LED components have been tested by an independent laboratory in accordance with IESNA LM-79 and LM-80.

RoHS:
Mercury and UV free. RoHS-compliant components.

FCC:
Complies with Part 15 of the FCC Rules

Other

5-Year Limited Warranty:
The RAB 5-year, limited warranty covers light output, driver performance and paint finish. RAB's warranty is subject to all terms and conditions found at rablighting.com/warranty.

Dimensions

