

PRODUCT DATASHEET

LED NFC PROGRAMMABLE DRIVER

OUTDOOR 100W UNV 1250mA DIM AUX12

IP65

tapTronic™ NFC LED Driver Constant Current Outdoor | Outdoor NFC programmable LED driver



Areas of application

- Area lights
- Industrial high bays
- Wall packs
- Décor landscape
- Cobraheads
- Bollards
- Hazardous locations

Product features

- Field-programmable via free app
- Dim to off – dim range 10-100 %
- Constant lumen output
- Soft start
- End of life
- Thermal protection
- DC Auxiliary output
- cULus Class P
- IP65
- App is multi-lingual: English/French/Spanish/Portuguese

TECHNICAL DATA

Additional product data

Ordering Abbreviation	LEDrv100UNV1250DIMAUX12P6NFC
Abbrev. With Packaging Info.	LEDrv100UNV1250DIMAUX12P6NFC 10/CS 1/SKU
UPC Code	0046135758546
NAED	75854
General Description	100W NFC Outdoor Constant Current LED Driver, 350 -1250mA programmable, Dim 0-10V w/ 10-100% range, 12V AUX, IP66, NFC=Near-Field Communication

Electrical data

Nominal Wattage	100.00 W
Nominal voltage	120...277 V
Supply Frequency	50...60 Hz

Dimensions & Weight

Length	240.50 mm
Width	60.96 mm
Height	38.10 mm
Product weight	1000.00 g

Application & Mounting

Dimming	Yes
Number of Lamps	1
Type of Dimming	0-10V



Capabilities


Dimming	Yes
---------	-----

Certificates & Standards

Certification Listing	RoHS / FCC
Type of protection	IP67

DOWNLOAD DATA

Spec Sheets and Product Documents	Document name
 Extended installation guide	installation guide tapTronic™ NFC LED Driver Constant Current
 Product Family Spec Sheet	ProPoint Industrial Linear Luminaire Cutsheet

Spec Sheets and Product Documents	Document name
 Product Family Spec Sheet	tapTronic™ NFC LED Driver Constant Current

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.