

Blue Lamp



Features

When reversing, it emits a blue light onto the floor in the direction of travel, alerting nearby vehicles and workers to the approach or movement of a forklift. By visually informing them of the approach or movement of vehicles, it supports safe work.



Specifications

Operating Voltage	8V~64V
Operating Current	2.0A (DC12V)
Operating Temperature	-40°C~+85°C
Water Resistance	JIS D 0203 S1
Rated Voltage	DC12V, DC24V (multiple)
Insulation Resistance	500MΩ or more (500V Mega)
Vibration Durability	JIS D 1601 (Type 3 B) Acceleration: 100m/s ² , Frequency: 67Hz, Vibration direction: 4 hours up and down, 2 hours left and right, 2 hours front and rear
Paint Adhesion	JIS K 5600-5-6 (General paint test method - Part 5: Mechanical properties of coating film - Section 6: Adhesion) cross-cut method was carried out. Of the six categories according to JIS K 5600-5-6, it must be classified as 0.
Reserve Voltage Characteristics	DC-30V is applied for 1 minute, and no abnormalities are observed in the operation
Electrostatic Property	ISO 10605 ED2.0:2008 Level 3 Category 2 was conducted, and after testing, there should be no abnormalities in operation
Corrosion Resistance	Meets JIS D 5500 4.12
Dust Durability	Meets JIS D 5500 4.9

Dimensions

