

Simplex® 6200



Features

Access Control

Mechanical pushbutton lock eliminates problems and costs associated with issuing, controlling, and collecting keys and cards. Provides fully mechanical exterior access by combination, while allowing free egress at all times by interior knob.

No Battery

Fully mechanical lock eliminates the material and labor expense of battery replacements

Locking Device

Cylindrical latch

Number of Codes

Single access code—one easy-to-manage code for all users

Programming

Lock is easily programmed via keypad without removing lock from the door

Handing

Factory-handed left; easily field reversible


Operation Modes

Pushbutton Access

Economical


A cost effective access control solution

Model 6202



- Combination Entry
- UL Listed Latch
- ½" (13 mm) Throw Floating Face Plate
- Backset 2¾" (60 mm)
- Primary Lock

Model 6204



- Combination Entry
- UL Listed Latch
- ½" (13 mm) Throw Floating Face Plate
- Backset 2¾" (70 mm)
- Primary Lock

Mechanical Features

<i>Construction</i>	All metal cast front housing, force-resistant, clutch-protected exterior thumbturn, unified interior trim plate, fixed interior knob
<i>Numeric Keypad</i>	Vandal resistant, solid metal pushbuttons
<i>Finishes</i>	Hard, durable powder paint finishes: Gold Tone (060), Almond (067), Black (085), and Gray (086) (Gold and Almond inside trim/plated Bright Brass) (Black and Gray inside trim/plated Satin Chrome)
<i>Latch</i>	1/2" (13 mm) throw latch, floating faceplate (UL listed)
<i>Backset</i>	2 3/4" (70 mm) or 2 3/8" (60 mm) backset
<i>Strike</i>	Standard strike plate
<i>Minimum Stile Recommended</i>	5" (127 mm)
<i>Weight</i>	4.5 lbs. (2 kg)

Installation

<i>Installation</i>	ASA 161 door preparation with two additional through bore holes. Lock can be inverted if the existing auxiliary lock obstructs installation.
<i>Door Thickness</i>	1 3/8" (35 mm) to 2 1/4" (57 mm); wood or metal
<i>Items Supplied Include</i>	Installation manual, full-scale template, combination change tool, and required installation hardware

Certification and Testing

<i>Durability</i>	Weather resistant
<i>Fire Rating</i>	3-hour UL/ULC fire rating for "A" labeled doors

Warranty

<i>Warranty</i>	1-year warranty
-----------------	-----------------

