

COBAGriP® Decking Strip
PRODUCT DATASHEET



FEATURES AND BENEFITS


- ' A fast and simple solution to provide slip resistance on decking and similar structures.
- ' Silicon carbide surface for high anti slip protection in both wet and dry conditions and the perfect solution to slippery decking during the winter months.
- ' Suitable for indoor and outdoor use and easily applied to wooden, metal or concrete surfaces.
- ' Suitable for use on decking, walkways, bridges, steps, construction environments, schools and leisure facilities.
- ' Simply bond or screw onto the existing floor surface. Made from 3 mm thick low profile sheet ensuring suitability with wheelchair traffic.
- ' Easy to cut to length.
- ' Available in a range of colours which meet the Equality Act requirements, including black, grey and yellow.
- ' Fire Tested to DIN 13501: Bfl – s1 (2018) & EN ISO 11925-2:2020 & EN ISO 9239-1:2010 (both 2021).
- ' Slip Tested to DIN 51130 – R13 & BS 7976-2 – low slip potential.

Technical Specification

Material	GRP
Product Height	3 mm
Min. Operating Temperature	-50°
Max. Operating Temperature	+90°
Environmental Resistance	Suitable for indoor and outdoor environments
Typical Applications	External walkways/decking areas
Installation Method	Bond or screw to surface
Cleaning Method	Brushing and flushing with a mild detergent
Fire Tested To	DIN 13501: Bfl – s1 (2018) & EN ISO 11925-2:2020 & EN ISO 9239-1:2010 (both 2021)
Guarantee	2 Years
Slip Tested To	DIN 51130 – R13 & BS 7976-2

Notes: Slip resistance specifications are based on the correct direction of travel i.e. perpendicular to the rails and inserts.

STYLES AND COLOURS



Yellow



Black



Grey

