


Sound XL

Combining the high-quality finish of a Trim-Tex vinyl bead with the versatility of compressible foam, Sound XL is a powerful all-in-one solution for sealing off head-of-wall joints to deliver high-performance ratings for smoke and sound. The attached foam adapts along uneven surfaces and provides a full $\frac{3}{4}$ " of building movement, making it an excellent choice for high-rises and other multi-story structures.

Installation Guide

Technical Specs



Scan Below for Installation Video



Before Installation:

Install drywall and leave a $\frac{3}{4}$ " gap between ceiling/adjacent structure and drywall. Measure, cut and dry fit the bead.

Step 1:

Coat both the bead and edge of drywall with Trim-Tex 847 Spray Adhesive.

Step 2:

Angle the foam into the gap and press mud leg against wall while ensuring that the flexible gasket is touching the ceiling/adjacent structure and is slightly compressed. Do not over-compress the flexible gasket or compressible foam.

Step 3:

Staple every 6"-8" using $\frac{1}{2}$ " staples.


Step 4:

Finish with drywall compound. Remove tear-off strips prior to sanding.


Note:

- To keep the drywall gap consistent, use an appropriately sized spacer on top of drywall.
- There should be no gaps left in joints between pieces. Additional sealant may be used at butt joint to ensure seamless joints.


Step 1:



Step 2:



Step 3:



Step 4:

