



Unpunched Casing Bead Submittal Sheet

STOCK NO.	A SIZE	LENGTH	PCS. PER BOX
3550	1/2"	10'	40
3575	3/4"	10'	40
3578	7/8"	10'	40
35100	1"	10'	40
35138	1 3/8"	10'	40
W/ HOLES	A SIZE	LENGTH	PCS. PER BOX
3575WP	3/4"	10'	40
3578WP	7/8"	10'	40
35138WP	1 3/8"	10'	40

Description: Finish strong with maximum coverage. This Unpunched Casing Bead features an extra wide 3 1/2" flange, ideal for clean terminations at foundations, windows, doors and other stop points. The solid, unpunched flange allows for precise, customizable fastening during installation. Available in weeped or unweeped options to suit your project needs.

Advantages: Made from exterior grade PVC. Provides a high impact resistant, rust-proof termination corner.


Applicable Standards: Rigid exterior grade PVC products made by Trim-Tex meet ASTM specifications C926, C1063, C1780, C1861, D1784 and D4216.

Installation: Trim-Tex recommends following established acceptable industry standard installation methods. All butt joints, intersections, and ends should be caulked at the time of installation using elastomeric sealant. When painting Trim-Tex Exterior products, please refer to our painting resources to ensure proper performance and prevent product defects such as warping, oil canning, and buckling.

Job Name _____

Contractor _____

Date _____



Approvals (Signatures or Stamps)