

Lap Siding Step Bead Submittal Sheet




STOCK NO.	A SIZE	B SIZE	LENGTH	PCS. PER BOX
SSB 75-50	3/4"	1/2"	10'	50
SSB 78-58	7/8"	5/8"	10'	50
SSB 100-50	1"	1/2"	10'	50
SSB 100-58	1"	5/8"	10'	50

Description: Simulate the crisp look of lap siding – using only stucco. The Lap Siding Step Bead mimics the clean lines of cement board siding using stucco alone, saving time and labor costs. A built-in double ground functions as a screed between adjoining bands, while grooved flanges enhance the bond to the stucco for a clean, durable finish.

Advantages: Made from exterior grade PVC. Provides a high impact resistant, rust-proof termination corner.

Applicable Standards: Rigid exterior grade PVC products made by Trim-Tex meet ASTM specifications C926, C1063, C1780, C1861, D1784 and D4216.

Installation: Trim-Tex recommends following established acceptable industry standard installation methods. All butt joints, intersections, and ends should be caulked at the time of installation using elastomeric sealant. When painting Trim-Tex Exterior products, please refer to our painting resources to ensure proper performance and prevent product defects such as warping, oil canning, and buckling.



Job Name _____

Contractor _____

Date _____

Approvals (Signatures or Stamps)