



## Continuous Soffit Vent Submittal Sheet

STOCK NO.	A SIZE	B SIZE	AIRFLOW/ LF	LENGTH	PCS. PER BOX
549-50	1/2"	2 3/8"	14 sq in.	10'	13
549-58	5/8"	2 3/8"	14 sq in.	10'	13
549-75	3/4"	2 3/8"	14 sq in.	10'	13
549-78	7/8"	2 3/8"	14 sq in.	10'	13
3549-50	1/2"	3"	15 sq in.	10'	13
3549-58	5/8"	3"	15 sq in.	10'	13
3549-75	3/4"	3"	15 sq in.	10'	13
4549-50	1/2"	4"	16 sq in.	10'	13
4549-58	5/8"	4"	16 sq in.	10'	13
4549-75	3/4"	4"	16 sq in.	10'	13
6549-50	1/2"	6"	18 sq in.	10'	10

**Description:** The Continuous Soffit Vent offers a clean, easy solution for venting soffit areas without breaking the budget. The wide flange makes installation simple, and it's made from tough, exterior-grade PVC that won't rust or corrode. Great paint adhesion and solid stucco bonding help maintain a crisp, finished look season after season.


**Advantages:** Made from exterior grade PVC. Provides a high impact resistant, rust-proof termination corner.

**Applicable Standards:** Rigid exterior grade PVC products made by Trim-Tex meet ASTM specifications C926, C1063, C1780, C1861, D1784 and D4216.

**Installation:** Trim-Tex recommends following established acceptable industry standard installation methods. All butt joints, intersections, and ends should be caulked at the time of installation using elastomeric sealant. When painting Trim-Tex Exterior products, please refer to our painting resources to ensure proper performance and prevent product defects such as warping, oil canning, and buckling.

Job Name \_\_\_\_\_

Contractor \_\_\_\_\_



Approvals (Signatures or Stamps)