


Casing Bead with 5" Flange Submittal Sheet




STOCK NO.	A SIZE	LENGTH	PCS. PER BOX
1050XL	1/2"	10'	40
1058XL	5/8"	10'	40
1075XL	3/4"	10'	40
1078XL	7/8"	10'	40

Description: The Casing Bead with 5" Flange is built for roofline terminations and other areas where extended flange coverage is a must. Its grooved flange enhances stucco bonding for a secure, long-lasting hold. It delivers sharp, professional edges where walls meet windows, doors, and other details. Made from tough, exterior-grade PVC, it stands up to rust, corrosion and harsh conditions.

Advantages: Made from exterior grade PVC. Provides a high impact resistant, rust-proof termination corner.

Applicable Standards: Rigid exterior grade PVC products made by Trim-Tex meet ASTM specifications C926, C1063, C1780, C1861, D1784 and D4216.

Installation: Trim-Tex recommends following established acceptable industry standard installation methods. All butt joints, intersections, and ends should be caulked at the time of installation using elastomeric sealant. When painting Trim-Tex Exterior products, please refer to our painting resources to ensure proper performance and prevent product defects such as warping, oil canning, and buckling.



Job Name _____

Contractor _____

Date _____

Approvals (Signatures or Stamps)