



175G5220

MCD202007T4CV1

MCD202007T4CV1
 VLT® Compact Starter MCD 202
 7 kW 18A:4-6: 354
 Three phase, 200-440 VAC
 Control voltage: 24 VAC/VDC
 (A) A-Frame

Model code: MCD202007T4CV1

VLT® Compact Starter MCD 200 from Danfoss includes two families of soft starters in the power range 7.5-110 kW. The series offers easy DIN rail mounting for sizes up to 30 kW, 2-wire or 3-wire start/stop control and excellent starting duty (4 x Ie for 6 seconds). Heavy starting rating at 4x Ie for 20 seconds. Compatible with grounded delta power systems.

PRODUCT DETAILS

Gross weight		2.9 Kilogram
Net weight		2.4 Kilogram
Volume		12.896 Liter
EAN		5702427098596
Product View (Switch)	GLBL	Global (Standard)
Product Group	MCD	VLT® Soft Starter MCD
MCD Series	202	202
Power Rating	007	7 kW 18A:4-6: 354
Phase	T	Three phase
Mains Voltage	4	200-440 VAC
Control Supply Voltage	CV1	24 VAC/VDC
Frame Size	A	(A) A-Frame
Typecode Part 1		MCD202007T4CV1
Product Catalog	NO_VIEW	NO VIEW
Modelcode01		MCD202007T4CV1
ECCN EU	Y901	Y901
ECCN US	EAR99	EAR99
Calculated Gross Weight [kg]		2.9
Calculated Net Weight [kg]		2.4
Vendor	ERR01	Cannot Determine Vendor
Recommended Factory	ERR01	Cannot Determine Vendor
Recommended Plant	ERR01	ERR01

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.