

MAXX Bendurol2**Section: 1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING****1.1 Product identifier**

Product name : MAXX Bendurol2

Product code : 117053E

Use of the
Substance/Mixture : Floor Stripper

Substance type: : Mixture

For professional users only.

Product dilution information : No dilution information provided.

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Floor stripper. Manual process

Recommended restrictions
on use : Reserved for industrial and professional use.**1.3 Details of the supplier of the safety data sheet**Company : Ecolab Ltd.
PO Box 11; Winnington Avenue
Northwich, Cheshire, United Kingdom CW8 4DX
+ 44 (0)1606 74488
ccs@ecolab.com**1.4 Emergency telephone number**Emergency telephone
number : +441618841235
+32-(0)3-575-5555 Trans-European

Date of Compilation/Revision : 14.04.2020

Version : 1.3

Section: 2. HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Eye irritation, Category 2

H319

2.2 Label elements**Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms :



MAXX BenduroI2

Signal Word	: Warning	
Hazard Statements	: H319	Causes serious eye irritation.
Precautionary Statements	: Prevention: P280e	Wear eye protection/face protection.

2.3 Other hazards

None known.

Section: 3. COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Hazardous components**

Chemical Name	CAS-No. EC-No. REACH No.	Classification REGULATION (EC) No 1272/2008	Concentration: [%]
2-phenoxyethanol	122-99-6 204-589-7 01-2119488943-21	Acute toxicity Category 4; H302 Eye irritation Category 2; H319	>= 5 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44	Eye irritation Category 2; H319	>= 5 - < 10
3-butoxypropan-2-ol	5131-66-8 225-878-4 01-2119475527-28	Skin irritation Category 2; H315 Eye irritation Category 2; H319	>= 5 - < 10
Alcohols, C13, branched, ethoxylated	69011-36-5 POLYMER	Acute toxicity Category 4; H302 Serious eye damage Category 1; H318	>= 1 - < 2.5
Sodium p- cumenesulphonate	15763-76-5 239-854-6 01-2119489411-37	Eye irritation Category 2; H319	>= 1 - < 2.5
Substances with a workplace exposure limit :			
monoethanolamine	141-43-5 205-483-3 01-2119486455-28	Acute toxicity Category 4; H302 Acute toxicity Category 4; H332 Acute toxicity Category 4; H312 Skin corrosion Sub-category 1B; H314 Chronic aquatic toxicity Category 3; H412 Specific target organ toxicity - single exposure Category 3; H335	>= 0.1 - < 0.25

For the full text of the H-Statements mentioned in this Section, see Section 16.

Section: 4. FIRST AID MEASURES**4.1 Description of first aid measures**

In case of eye contact	: Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention.
In case of skin contact	: Rinse with plenty of water.
If swallowed	: Rinse mouth. Get medical attention if symptoms occur.
If inhaled	: Get medical attention if symptoms occur.

MAXX BenduroI2

4.2 Most important symptoms and effects, both acute and delayed

See Section 11 for more detailed information on health effects and symptoms.

4.3 Indication of immediate medical attention and special treatment needed

Treatment : Treat symptomatically.

Section: 5. FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media : None known.

5.2 Special hazards arising from the substance or mixture

Specific hazards during firefighting : Not flammable or combustible.

Hazardous combustion products : Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NOx)
Sulphur oxides

5.3 Advice for firefighters

Special protective equipment for firefighters : Use personal protective equipment.

Further information : Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations. In the event of fire and/or explosion do not breathe fumes.

Section: 6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel : Ensure clean-up is conducted by trained personnel only. Refer to protective measures listed in sections 7 and 8.

Advice for emergency responders : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials.

6.2 Environmental precautions

Environmental precautions : Do not allow contact with soil, surface or ground water.

6.3 Methods and materials for containment and cleaning up

Methods for cleaning up : Stop leak if safe to do so. Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth,

MAXX BenduroI2

diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Flush away traces with water. For large spills, dike spilled material or otherwise contain material to ensure runoff does not reach a waterway.

6.4 Reference to other sections

See Section 1 for emergency contact information.
 For personal protection see section 8.
 See Section 13 for additional waste treatment information.

Section: 7. HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling : Avoid contact with skin and eyes. Use only with adequate ventilation. Wash hands thoroughly after handling. In case of mechanical malfunction, or if in contact with unknown dilution of product, wear full Personal Protective Equipment (PPE).

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers : Keep out of reach of children. Keep container tightly closed. Store in suitable labeled containers.

Storage temperature : -5 °C to 40 °C

7.3 Specific end uses

Specific use(s) : Floor stripper. Manual process

Section: 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67.5 mg/m ³	UKCOSSTD
		STEL	15 ppm 101.2 mg/m ³	UKCOSSTD
monoethanolamine	141-43-5	TWA	1 ppm 2.5 mg/m ³	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		
		STEL	3 ppm 7.6 mg/m ³	UKCOSSTD
Further information	Sk	Can be absorbed through the skin. The assigned substances are those for which there are concerns that dermal absorption will lead to systemic toxicity.		

DNEL

MAXX BenduroI2

<p>2-(2-butoxyethoxy)ethanol</p>	<p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 101.2 mg/m3</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 20 mg/kg</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 67.5 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Short-term - local Value: 67.5 mg/m3</p>
<p>triethanolamine</p>	<p>: End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 5 mg/m3</p> <p>End Use: Workers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 5 mg/m3</p> <p>End Use: Workers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 6.3 mg/cm2</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term systemic effects Value: 1.25 mg/m3</p> <p>End Use: Consumers Exposure routes: Inhalation Potential health effects: Long-term local effects Value: 1.25 mg/m3</p> <p>End Use: Consumers Exposure routes: Dermal Potential health effects: Long-term systemic effects Value: 3.1 mg/cm2</p> <p>End Use: Consumers Exposure routes: Ingestion Potential health effects: Long-term systemic effects Value: 13 ppm</p>

PNEC

MAXX BenduroI2

2-(2-butoxyethoxy)ethanol	: Fresh water Value: 1 mg/l Marine water Value: 0.1 mg/l Intermittent use/release Value: 3.9 mg/l Sewage treatment plant Value: 200 mg/l Sediment Value: 4 mg/kg Soil Value: 0.4 mg/kg Oral Value: 56 mg/kg
triethanolamine	: Fresh water Value: 0.32 mg/l Marine water Value: 0.032 mg/l Intermittent use/release Value: 5.12 mg/l Fresh water sediment Value: 1.7 mg/kg Marine sediment Value: 1.7 mg/kg Sewage treatment plant Value: 10 mg/l Soil Value: 0.151 mg/kg

8.2 Exposure controls

Appropriate engineering controls

Engineering measures : Good general ventilation should be sufficient to control worker exposure to airborne contaminants.

Individual protection measures

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Remove and wash contaminated clothing before re-use. Wash face, hands and any exposed skin thoroughly after handling.

MAXX BenduroI2

- Eye/face protection (EN 166) : Safety glasses with side-shields
- Hand protection (EN 374) : No special protective equipment required.
- Skin and body protection (EN 14605) : No special protective equipment required.
- Respiratory protection (EN 143, 14387) : None required if airborne concentrations are maintained below the exposure limit listed in Exposure Limit Information. Use certified respiratory protection equipment meeting EU requirements(89/656/EEC, (EU) 2016/425), or equivalent, when respiratory risks cannot be avoided or sufficiently limited by technical means of collective protection or by measures, methods or procedures of work organization.

Environmental exposure controls

- General advice : Consider the provision of containment around storage vessels.

Section: 9. PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

- Appearance : liquid
- Colour : clear, colourless
- Odour : solvent-like
- pH : 10.1 - 10.6, 100 %
- Flash point : Not applicable.
- Odour Threshold : Not applicable and/or not determined for the mixture
- Melting point/freezing point : Not applicable and/or not determined for the mixture
- Initial boiling point and boiling range : > 100 °C
- Evaporation rate : Not applicable and/or not determined for the mixture
- Flammability (solid, gas) : Not applicable and/or not determined for the mixture
- Upper explosion limit : Not applicable and/or not determined for the mixture
- Lower explosion limit : Not applicable and/or not determined for the mixture
- Vapour pressure : Not applicable and/or not determined for the mixture
- Relative vapour density : Not applicable and/or not determined for the mixture
- Relative density : 1.006 - 1.016
- Water solubility : soluble
- Solubility in other solvents : Not applicable and/or not determined for the mixture
- Partition coefficient: n-octanol/water : Not applicable and/or not determined for the mixture
- Auto-ignition temperature : Not applicable and/or not determined for the mixture
- Thermal decomposition : Not applicable and/or not determined for the mixture
- Viscosity, kinematic : Not applicable and/or not determined for the mixture

MAXX BenduroI2

Explosive properties : Not applicable and/or not determined for the mixture
Oxidizing properties : The substance or mixture is not classified as oxidizing.

9.2 Other information

Not applicable and/or not determined for the mixture

Section: 10. STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

No dangerous reaction known under conditions of normal use.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

None known.

10.6 Hazardous decomposition products

Depending on combustion properties, decomposition products may include following materials:
Carbon oxides
nitrogen oxides (NO_x)
Sulphur oxides

Section: 11. TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Information on likely routes of exposure : Inhalation, Eye contact, Skin contact

Product

Acute oral toxicity : Acute toxicity estimate : > 2,000 mg/kg
Acute inhalation toxicity : There is no data available for this product.
Acute dermal toxicity : There is no data available for this product.
Skin corrosion/irritation : There is no data available for this product.
Serious eye damage/eye irritation : There is no data available for this product.

MAXX BenduroI2

- Respiratory or skin sensitization : There is no data available for this product.
- Carcinogenicity : There is no data available for this product.
- Reproductive effects : There is no data available for this product.
- Germ cell mutagenicity : There is no data available for this product.
- Teratogenicity : There is no data available for this product.
- STOT - single exposure : There is no data available for this product.
- STOT - repeated exposure : There is no data available for this product.
- Aspiration toxicity : There is no data available for this product.

Components

- Acute oral toxicity : 2-phenoxyethanol
LD50 rat: 2,000 mg/kg
- 2-(2-butoxyethoxy)ethanol
LD50 rat: 3,306 mg/kg
- 3-butoxypropan-2-ol
LD50 rat: 2,500 mg/kg
- Alcohols, C13, branched, ethoxylated
LD50 rat: > 500 mg/kg
- Sodium p-cumenesulphonate
LD50 rat: > 7,000 mg/kg
- monoethanolamine
LD50 rat: 1,089 mg/kg

Components

- Acute inhalation toxicity : monoethanolamine
4 h LC50 rat: > 1.6 mg/l
Test atmosphere: dust/mist

Components

- Acute dermal toxicity : 2-phenoxyethanol
LD50 rabbit: 2,250 mg/kg
- 2-(2-butoxyethoxy)ethanol
LD50 rabbit: 2,764 mg/kg
- 3-butoxypropan-2-ol
LD50 rat: 2,193 mg/kg
- monoethanolamine
LD50 rabbit: 1,025 mg/kg

Potential Health Effects

MAXX BenduroI2

- Eyes : Causes serious eye irritation.
- Skin : Health injuries are not known or expected under normal use.
- Ingestion : Health injuries are not known or expected under normal use.
- Inhalation : Health injuries are not known or expected under normal use.
- Chronic Exposure : Health injuries are not known or expected under normal use.

Experience with human exposure

- Eye contact : Redness, Pain, Irritation
- Skin contact : No symptoms known or expected.
- Ingestion : No symptoms known or expected.
- Inhalation : No symptoms known or expected.

Section: 12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

- Environmental Effects : This product has no known ecotoxicological effects.

Product

- Toxicity to fish : no data available
- Toxicity to daphnia and other aquatic invertebrates : no data available
- Toxicity to algae : no data available

Components

- Toxicity to fish : 2-phenoxyethanol
96 h LC50 Fish: > 220 mg/l
- 2-(2-butoxyethoxy)ethanol
96 h LC50 Fish: 1,300 mg/l
- Alcohols, C13, branched, ethoxylated
96 h LC50 Fish: 3 mg/l
- Sodium p-cumenesulphonate
96 h LC50 Oncorhynchus mykiss (rainbow trout): > 1,000 mg/l

Components

- Toxicity to daphnia and other aquatic invertebrates : 3-butoxypropan-2-ol
48 h EC50: > 1,000 mg/l
- Alcohols, C13, branched, ethoxylated
48 h EC50 Daphnia magna (Water flea): 1.5 mg/l
- monoethanolamine
48 h LC50: 65 mg/l

Components

MAXX BenduroI2

Toxicity to algae : Sodium p-cumenesulphonate
96 h EC50 Pseudokirchneriella subcapitata (algae): > 230 mg/l

12.2 Persistence and degradability

Product

Biodegradability : The surfactants contained in the product are biodegradable according to the requirements of the detergent regulation 648/2004/EC

Components

Biodegradability : 2-phenoxyethanol
Result: Readily biodegradable.

2-(2-butoxyethoxy)ethanol
Result: Readily biodegradable.

3-butoxypropan-2-ol
Result: Readily biodegradable.

Alcohols, C13, branched, ethoxylated
Result: Biodegradable

Sodium p-cumenesulphonate
Result: Readily biodegradable.

monoethanolamine
Result: Readily biodegradable.

12.3 Bioaccumulative potential

no data available

12.4 Mobility in soil

no data available

12.5 Results of PBT and vPvB assessment

Product

Assessment : This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

no data available

Section: 13. DISPOSAL CONSIDERATIONS

Dispose of in accordance with the European Directives on waste and hazardous waste. Waste codes should be assigned by the user, preferably in discussion with the waste disposal authorities.

13.1 Waste treatment methods

MAXX BenduroI2

- Product : Where possible recycling is preferred to disposal or incineration. If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility.
- Contaminated packaging : Dispose of as unused product. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers. Dispose of in accordance with local, state, and federal regulations.
- Guidance for Waste Code selection : Organic wastes containing dangerous substances. If this product is used in any further processes, the final user must redefine and assign the most appropriate European Waste Catalogue Code. It is the responsibility of the waste generator to determine the toxicity and physical properties of the material generated to determine the proper waste identification and disposal methods in compliance with applicable European (EU Directive 2008/98/EC) and local regulations.

Section: 14. TRANSPORT INFORMATION

The shipper/consignor/sender is responsible to ensure that the packaging, labeling, and markings are in compliance with the selected mode of transport.

Land transport (ADR/ADN/RID)

- 14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods

Air transport (IATA)

- 14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods
14.6 Special precautions for user : Not dangerous goods

Sea transport (IMDG/IMO)

- 14.1 UN number : Not dangerous goods
14.2 UN proper shipping name : Not dangerous goods
14.3 Transport hazard class(es) : Not dangerous goods
14.4 Packing group : Not dangerous goods
14.5 Environmental hazards : Not dangerous goods

MAXX BenduroI2

14.6 Special precautions for user : Not dangerous goods
 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code : Not dangerous goods

Section: 15. REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

according to Detergents Regulation EC 648/2004 : less than 5 %: Anionic surfactants, Non-ionic surfactants
 Preservation agents:
 2-phenoxyethanol

National Regulations

Take note of Dir 94/33/EC on the protection of young people at work.

Other regulations : The Chemicals (Hazard Information and Packaging for Supply) Regulations.
 The Control of Substances Hazardous to Health Regulations.
 Health and Safety at Work Act.

15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out on the product.

Section: 16. OTHER INFORMATION

Procedure used to derive the classification according to REGULATION (EC) No 1272/2008

Classification	Justification
Eye irritation 2, H319	Calculation method

Full text of H-Statements

H302 Harmful if swallowed.
 H312 Harmful in contact with skin.
 H314 Causes severe skin burns and eye damage.
 H315 Causes skin irritation.
 H318 Causes serious eye damage.
 H319 Causes serious eye irritation.
 H332 Harmful if inhaled.
 H335 May cause respiratory irritation.
 H412 Harmful to aquatic life with long lasting effects.

Full text of other abbreviations

ADN – European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS – Australian Inventory of Chemical Substances; ASTM – American Society for the Testing of Materials; bw – Body weight; CLP – Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR – Carcinogen, Mutagen or Reproductive Toxicant; DIN – Standard of the German Institute for Standardisation; DSL – Domestic Substances List (Canada); ECHA – European Chemicals Agency; EC-Number – European Community number; ECx – Concentration associated with x% response; ELx – Loading rate associated with x% response; EmS – Emergency Schedule; ENCS – Existing and New Chemical Substances (Japan); ErCx – Concentration associated with x% growth rate response;

MAXX BenduroI2

GHS – Globally Harmonized System; GLP – Good Laboratory Practice; IARC – International Agency for Research on Cancer; IATA – International Air Transport Association; IBC – International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 – Half maximal inhibitory concentration; ICAO – International Civil Aviation Organization; IECSC – Inventory of Existing Chemical Substances in China; IMDG – International Maritime Dangerous Goods; IMO – International Maritime Organization; ISHL – Industrial Safety and Health Law (Japan); ISO – International Organisation for Standardization; KECI – Korea Existing Chemicals Inventory; LC50 – Lethal Concentration to 50 % of a test population; LD50 – Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL – International Convention for the Prevention of Pollution from Ships; n.o.s. – Not Otherwise Specified; NO(A)EC – No Observed (Adverse) Effect Concentration; NO(A)EL – No Observed (Adverse) Effect Level; NOELR – No Observable Effect Loading Rate; NZIoC – New Zealand Inventory of Chemicals; OECD – Organization for Economic Co-operation and Development; OPPTS – Office of Chemical Safety and Pollution Prevention; PBT – Persistent, Bioaccumulative and Toxic substance; PICCS – Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR – (Quantitative) Structure Activity Relationship; REACH – Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID – Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT – Self-Accelerating Decomposition Temperature; SDS – Safety Data Sheet; TCSI – Taiwan Chemical Substance Inventory; TRGS – Technical Rule for Hazardous Substances; TSCA – Toxic Substances Control Act (United States); UN – United Nations; vPvB – Very Persistent and Very Bioaccumulative

Prepared by : Regulatory Affairs

Numbers quoted in the MSDS are given in the format: 1,000,000 = 1 million and 1,000 = 1 thousand. 0.1 = 1 tenth and 0.001 = 1 thousandth

REVISED INFORMATION: Significant changes to regulatory or health information for this revision is indicated by a bar in the left-hand margin of the SDS.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Annex: Exposure Scenarios

Exposure Scenario: Floor stripper. Manual process

Life Cycle Stage : Widespread use by professional workers
Product category : **PC35** Washing and cleaning products (including solvent based products)

Contributing scenario controlling environmental exposure for:

Environmental release category : **ERC8a** Wide dispersive indoor use of processing aids in open systems
Daily amount per site : 7.5 kg

MAXX BenduroI2

Type of Sewage Treatment Plant : Municipal sewage treatment plant

Contributing scenario controlling worker exposure for:

Process category : **PROC10** Roller application or brushing

Exposure duration : 480 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Respiratory Protection : No

Skin Protection : Yes: See Section 8

Contributing scenario controlling worker exposure for:

Process category : **PROC8a** Transfer of substance or preparation (charging/ discharging) from/ to vessels/ large containers at non-dedicated facilities

Exposure duration : 60 min

Operational conditions and risk management measures : Indoor

Local Exhaust Ventilation is not required

General ventilation Ventilation rate per hour 1

Skin Protection : Yes: See Section 8

Respiratory Protection : No