



TP-BC72-600

DATA SHEET

600W 72V Battery Charger

Features

- 72V 600W Total Power
- Over-Voltage, Over-Current, Reverse-Current, Over-Load, Short-Circuit Protections
- Led indicator: Red=Charging, Green=Battery Full/Float Charge
- CE Certification



Applications

- Wireless Base Stations, Cellular Base Stations
- Surveillance Systems
- Battery Backup Systems

Description

The **TP-BC72-600** battery chargers provide up to 600W of total charging power. The battery charger is compatible with GEL/AGM type sealed lead acid batteries.

The charger has various protections for reverse current, short-circuit, over-load, over-voltage, and over-current.

There is an LED which indicates charging (Red) or battery full (Green). The unit comes with a removeable AC cord with a North American Plug. The units are can work from 90VAC to 240VAC (selectable via switch).



Specifications

TP-BC72-600	
Total Power Available (for Load and Battery charging)	600W
Nominal Battery Voltage	72VDC
Battery Charge Max Current	6A
Battery Charger Voltage	88.2V
Battery Float Voltage	82.8V
Efficiency	>88%
DC Output Cable	2 Wire 14AWG ; 1.2m (48") long cable Brown = V+, Blue = V-
AC Input Connector	IEC C14
AC Power Cord	IEC C13 to Nema 5-15P, 1.2m (48")
AC Power Input	120VAC / 240VAC , 50/60Hz
Hi-Pot Test	1500VAC / 10mA / 1min
Insulation Resistance	>10MΩ, 500VDC
Operating Temperature	-10 to +40C (14 to +104°F)
Operating Humidity (RH)	5% to 90% (non condensing)
Storage Temperature	-40 to +70°C (-40 to +158°F)
Storage Humidity	5% to 95% (non-condensing)
Standards Compliance	CE, EN60335-1:2002 and EN60335-2-29:2002
MTBF (Mean Time Between Failure)	>50,000 hrs
Dimensions (LxWxH)	216 x 120 x 76mm (8.5 x 4.75 x 3")
Weight	1.95kg (4.3lb)
Warranty	2 Years



System Ordering:

TP-BC72-600 600W Battery Charger, 88.2V 6A, with US Power Cord*

*Add an "E" suffix for Euro power cord

For further information contact:

Tyconsystems.com

